


PAINTEX-4

Acrylic white crack filling compound



DESCRIPTION

Paintex-4 India's first acrylic crack filling compound is of a professional quality product. Paintex-4 prevents air and moisture from passing through cracks and joints, offers excellent flexibility to resist expansion and contraction without cracking. Paintable with latex and oil based paints. Useful for both interior as well as exterior

CHARACTERISTICS


- | | |
|---------------------------------|----------------------|
| • Colour | white and light grey |
| • Consistency | smooth and creamy |
| • Odour | Very mild |
| • Vehicle | Acrylic polymer |
| • Volatile | water |
| • Tooling time | 10 minutes |
| • Track free time | 30 minutes |
| • Temperature service range | -20°C to 90°C. |
| • Temperature application range | 3°C to 40°C. |
| • Freeze thaw stability | passes 5 cycles |
| • Paintability | yes |
| • Shelf life | 18 Months |
| • Max Gap filling capacity | up to 12 mm |

APPLICATION

- Window and door
- Frames corner
- Joints baseboard
- Moulding
- Vents
- Sliding and trim
- Other gaps & openings

PAINTEX-4

Acrylic white crack filling compound



EXCELLENT ADHESION ON

- Concrete
- Plaster
- Brick
- Drywall
- Painted surface
- Wood
- Metal

SURFACE PREPARATION AND APPLICATION

- Remove old caulk from surface.
- Make sure that surface is clean, dry and free of loose debris
- Trim the nozzle to the desired bead size
- Then puncture the foil using any pointed object.
- Load the cartridge into caulking gun.
- Hold the cartridge at a 45 angle and fill the seam with ample amount of sealant.

PACKING

Standard packing : 350 gm. Cartridge and 1 kg. tin

Colour : white or light grey after drying

PRECAUTION

Do not use in high abrasion area or underwater.

SHELF LIFE

24 Months.